

YOU WILL NEED

- Fabric A (print) one (1) fat quarter
- Fabric B (white print) one (1) fat eighth
- Fabric C (dark pink) one (1) fat quarter
- Fabric D (light peach) one (1) fat eighth
- Fabric E (dark peach) one (1) fat eighth
- Fabric F (light pink) one (1) fat eighth
- Fabric G (black) one (1) fat eighth
- Backing fabric: 26in square
- Batting: 26in square
- Binding: ¼yd

FINISHED SIZE

■ 24in square

NOTES

- Seam allowances are ¼in, unless otherwise noted.
- Press seams open, unless otherwise instructed.
- ■WOF width of fabric.
- RST right sides together.
- HST Half square Triangle.
- Wash and press all fabrics well before cutting.





MAKE MORE VERSIONS OF THESE 24IN BLOCKS AND COMBINE TO MAKE A FULL-SIZE QUILT

CUTTING OUT


- From Fabric A cut:
- Two (2) 7¼in squares.
- One (1) 5½ in square.
- Two (2) 4¾in squares.
- Four (4) 2½ in squares.
- 7 From Fabric B cut:
- Two (2) 71/4in squares.
- From Fabric C cut:

 Two (2) 7½in squares.
- Two (2) 5½in squares.
- From Fabric D cut: Two (2) 7½in squares.
- From Fabric E cut: **J** ■ Four (4) 5½in squares.

- From Fabric F cut:
- 0 Four (4) 5½ in squares.
- **7** From Fabric G cut:
- One (1) 5½ in square.
- Two (2) 4¾in squares.
- **Q** From your binding fabric cut: 0 ■ Three (3) 2¼in x WOF strips.

HALF-SQUARE TRIANGLES

9 To make two HSTs at once, pair two squares RST and draw a diagonal line from corner to corner on the back of one. Sew ¼in away on both sides of the line (Fig A). Cut on the line (Fig B). Press open and square up to the specified size (Fig C). This makes two HSTs.



10 Pair the following 5½ in squares and make HSTs, using the HST instructions in step 9. Make one Fabric C/G pair, one Fabric A/C pair, two Fabric E/E pairs and two Fabric F/F pairs. Once sewn, trim each HST to 4¾ in square.

11 Pair each of your Fabric A 7¼in squares with a Fabric B 7¼in square and make HSTs as before. Carefully trim each HST to 6½in square.

12 Pair each of your Fabric C 7½ in squares with a Fabric D 7½ in square and make HSTs as before, trimming each one to 6¾ in.

MAKING THE CORNER UNITS

13 Place one of your 2½ in squares of Fabric A on top of the Fabric B corner of your 6½ in square HST and draw a diagonal line from corner to corner. Sew on this line


(Fig D). Cut 1/4 in away from your sewn line towards the outer corner (Fig E). Press open (Fig F). Make four of these units.

14 Cut your Fabric C/D HSTs in half with a line running perpendicular to your seam (Fig G). Place these new triangles on either side of the block from step 13, as shown (Fig H) and sew to complete one corner unit. Make four corner units.


ASSEMBLING THE QUILT

15 Using all of your 4¾in HSTs and your remaining 4¾in squares of Fabrics A and G, sew together in four rows of four as shown (Fig I). Next, make sure that the seams of your Fabric E/E and Fabric F/F HSTs are all facing the right directions. They should form a diamond shape when arranged correctly.









17 Centre one corner unit along one of the sides of your centre panel. Sew in place (Fig K). Repeat with the remaining corner units to complete the quilt top.

18 Make a quilt sandwich and baste, using your preferred method. Quilt as desired. Nicole used her walking foot for some straight line quilting on her mini.

10 Trim away any excess batting and

backing fabric and square up.



20 Sew your binding strips together end to end with diagonal seams. Fold along the full length, wrong sides together, and press. Machine sew the binding to the front of the quilt, then fold it over to the back and hand stitch in place to finish.



Nicole Calver

Nicole's signature style combines classic quilting techniques with modern prints and colour palettes

snipssnippets.ca



See this project demonstrated live on air 3 May 2018

- Live on Freeview 78 and Sky 678 8am 12noon
- Online at sewingquarter.com
- Catch up with the show on youtube.com/sewingquarter
- Kits available online from 4 May