



GO! Falling Diamonds Quilt

finished size 48½" x 48½"



Fabric provided by Moda Fabrics,

GO!® DIES USED

- GO! Half Square-21/4" Finished Triangle (55147)
- GO! Square-23/4" (21/4" Finished) (55395)
- GO! Strip Cutter-2½" (2" Finished) (55017 or 55014)
- GO! Strip Cutter-41/2" (4" Finished) (55054)

FABRIC REQUIREMENTS

- Fabric 1 (White)—3¾ yards (includes border and binding)
- Fabric 2—¾ yard
- M Fabric 3—²/₃ yard
- Nabric 4—⅓ yard
- Batting-60" x 60"
- Backing—3½ yards

TIP: Width of fabric (WOF) yields: 14—21/4" finished half square triangles

1 yard yields: 182—21/4" finished half square triangles

CUTTING DIRECTIONS

Fabric 1:

- Cut 108—2¾" squares
- Cut 216—21/4" finished half square triangles
- Cut 6—4½" strips across the width of the fabric (WOF) for outer border
- Cut 6—2½" strips across the WOF for the binding

• Cut 108—21/4" finished half square triangles


• Cut 72—21/4" finished half square triangles


Fabric 4:

• Cut 36—21/4" finished half square triangles

SEWING DIRECTIONS

- 1. Lay out one Fabric #1 and one Fabric #2, 21/4" finished half square triangles (HST) as shown.
- 2. Pin and sew together to form one half square triangle Unit #1. Press seams towards the darker color. Make a total of 108, Unit #1, 21/4" finished HST.





- 5. Pin and sew into rows. Press seams in opposite directions.
- 6. Pin and sew rows together. Press seams in opposite directions.
- 7. Make a total of 36 blocks. Square blocks up to $7\frac{1}{2}$ " x $7\frac{1}{2}$ ".
- 8. Lay out the 36 blocks as shown.




Unit #1



Unit #2



Unit #3







2 of 2

SEWING DIRECTIONS CONT.

- 9. Pin and sew blocks into rows. Press seams in opposite directions.
- 10. Pin and sew rows together. Press seams in opposite directions.
- 11. Pin and sew border strips into one long strip along the short ends.
- 12. Cut two border strips the length of the quilt top.
- 13. Pin and sew border strips onto the sides of the quilt top. Press towards the border strips.
- 14. Cut two border strips the width of the quilt top.
- 15. Pin and sew border strips the width of the quilt top. Press towards the border strips.

QUILTING AND FINISHING

- Layer quilt top with batting and backing.
- 2. Pin or baste layers together.
- 3. Model was custom machine quilted.
- 4. Add binding, mitering the corners.